



API600 VALVE TRIM CHART

API600 Trim Number Chart

Trim	Mterial	Seat	Disc	Backseat	Stem	Notes
1	410	410	410	410	410	
2	304	304	304	304	304	
3	F310	310	310	310	310	
4	Hard 410	Hard 410	Hard 410	410	410	Seats 750 BHN min.
5	Hardfaced	Stellite	Stellite	410	410	
5A	Hardfaced	Ni-Cr	Ni-Cr	410	410	
6	410 and Cu-Ni	Cu-Ni	410	410	410	
7	410 and Hard 410	Hard 410	Hard 410	410	410	Seats 750 BHN min.
8	410 and Hardfaced	Stellite	410	410	410	
8A	410 and Hardfaced	Ni-Cr	410	410	410	
9	Monel	Monel	Monel	Monel	Monel	
10	316	316	316	316	316	
11	Monel and Hardfaced	Stellite	Monel	Monel	Monel	
12	316 and Hardfaced	Stellite	316	316	316	
13	Alloy 20	Alloy 20	Alloy 20	Alloy 20	Alloy 20	
14	Alloy 20 and Hardfaced	Stellite	Alloy 20	Alloy 20	Alloy 20	
15	304 and Hardfaced	Stellite	Stellite	304	304	
16	316 and Hardfaced	Stellite	Stellite	316	316	
17	347 and Hardfaced	Stellite	Stellite	347	347	
18	Alloy 20 and Hardfaced	Stellite	Stellite	Alloy 20	Alloy 20	

NOTE: The material and data of site is for general information. For specific performance data, proper material selection and special design, consult us freely.

Although every attempt has been made to ensure correct information, Sangong reserves the right to change designs, materials or specifications without notice

Contact information:

Sangong Flow Control Co., Limited
Add: Wuxing Industrial Zone , Oubei, Wenzhou, China
Tel: +86 577-6696-5396 Fax: +86 577-5684-6726
Email: info@sangongvalve.com
Website: www.sangongvalve.com